

VELS E-4,L-4

V-STEEL E-LUG S



The V-STEEL E-LUG S PREMIUM radial tire offers maximum heat dissipation and improved cut resistance for improved productivity and lower operating costs.

SPECIALIZED FEATURES

- Deep non-directional rock tread
- Special compounds provide exceptional wear and cut resistance
- Certain sizes feature low profile, low pressure technologies

VELS E-4,L-4

V-STEEL E-LUG S



CATEGORY	SIZE	PLY/STAR RATING	COMPOUND/ CONSTRUCTION	TRA	ARTICLE #	AVG. WT.	OTD (32ND)	OVERALL DIAMETER	OVERALL WIDTH
SMALL TUBELESS	18.00R25	2*	E1A	E-4	261432	780	63	64.5	20.3
	18.00R25	2*	E2A LS	E-4	423637	780	63	64.5	20.3
LARGE TUBELESS	18.00R33	2*	E1A	E-4	275867	960	61	73.1	20.2
	18.00R33	2*	E2A	E-4	276316	960	61	73.1	20.2
	18.00R33	2*	E2A LS	E-4	422177	960	61	73.1	20.2
	18.00R33	3*	IDU	L-4	429736	940	61	73.1	20.2
	21.00R35	2*	E2A	E-4	276324	1,470	74	80.5	22.7
	31/90R49 +	2*	E1A	E-4	424706	3,180	84	106.1	30.4
GIANT TUBELESS	31/90R49 +	2*	E2A	E-4	424714	3,180	84	106.1	30.4
	31/90R49 +	2*	E2A LS	E-4	424722	3,180	84	106.1	30.4
	37.00R57 ‡	2*	E3A LH	E-4	424587	6,100	97	133.4	41.1
	40.00R57 •	2*	E1A	E-4	421715	8,040	115	140.2	44.4
	40.00R57 •	2*	E2A	E-4	418897	8,040	115	140.2	44.4
	40.00R57 •	2*	E2A LS	E-4	421723	8,040	115	140.2	44.4
	40.00R57 •	2*	E3A	E-4	419621	8,040	115	140.2	44.4
	46/90R57 +	2*	E1A	E-4	423246	8,430	115	140.0	45.1
	46/90R57 +	2*	E2A	E-4	423440	8,430	115	140.0	45.1
	50/90R57 *	2*	E1A	E-4	422363	10,370	115	150.6	50.5
	50/90R57 •	2*	E2A	E-4	422371	10,370	115	150.6	50.5
	50/90R57 •	2*	E2A LS	E-4	422932	10,370	115	150.6	50.5
	50/90R57 •	2*	E3A	E-4	422398	10,370	115	150.6	50.5

LH: Long Haul
LS: Special Cut Resistant

BRIDGESTONE
OFF THE ROAD TIRES